

## Application

- Horizontal and building backbone cable.
- Support current and future **Category 5 enhanced** applications, such as:  
100 Base TX, 100 Base VG AnyLan, 155 ATM and 1000 Base-T (**Gigabit Ethernet**), FDDI.

## Key features and Standards

- General standards: **ISO/IEC 11801 2<sup>nd</sup> edition (2002)**, **EN 50173 2<sup>nd</sup> edition (2001)**, **ANSI/TIA/EIA 568-b.2 (2002)**
- Provides extended performance far in excess of industry standards
- Ideal for use in high bandwidth applications up to 350 MHz

## Construction & Dimensions



- Construction: Unshielded 4 twisted bonded pairs
- Conductor: Solid bare copper
- Conductor diameter: AWG 24 (0,51 mm)
- Conductor insulation material: Polyolefine
- Diameter over insulation: 0,95 mm
- Ripcord: Polyester
- Jacket material: FRNC
- Outer diameter: 5,0 mm

Pair 1	White-Blue/Blue
Pair 2	White-Orange/Orange
Pair 3	White-Green/Green
Pair 4	White-Brown/Brown

Colour identification according to IEC 60304

## Electrical characteristics (at 20 °C)

Nominal mutual capacitance at 1 kHz	50 nF/km
Maximum conductor DCR	93.5 Ohm/km
NVP - Nominal Velocity of Propagation	0.70 c
SKEW – Propagation delay difference (100 MHz)	typical $\leq$ 10 ns/100m
Impedance 1-100 MHz	100 $\pm$ 15 Ohm
Impedance 100-200 MHz	100 $\pm$ 18 Ohm
Impedance 200-310 MHz	100 $\pm$ 20 Ohm
Impedance 310-350 MHz	100 $\pm$ 22 Ohm

## General and environmental characteristics

Temperature range - operation	-20°C - +80°C
Temperature range - installation	+0°C - +50°C
Minimum bending radius - operation	6 mm
Minimum bending radius - installation	40 mm
Maximum pulling tension	80 N
Flame retardancy	IEC 332-1
Caloric value	298 kJ/m
Weight (approx.)	30 kg/km
Maximum operating voltage	300 V rms
Maximum continuous current per conductor (25°C)	1.4 A

### Electrical characteristics (at 20 °C)

#### Attenuation

Frequency	1	4	10	16	20	31.2	62.5	100	155	200	310	350	MHz
Spec. (Max.) <sup>1)</sup>	-	4.1	6.5	8.3	9.3	11.7	17.0	22.0	28.1	32.4	41.8	44.9	dB/100m
Typical	[1.9]	3.9	6.2	7.9	8.9	11.2	16	19.8	25.0	28.5	32.0	38.5	dB/100m

#### NEXT (Near end crosstalk)

Frequency	1	4	10	16	20	31.2	62.5	100	155	200	310	350	MHz
Spec. (Min.) <sup>1)</sup>	-	56.3	50.3	47.3	45.8	42.9	41.4	35.3	32.4	30.8	29.3	27.1	dB/100m
Typical	[73]	64	58	55	54	51	47	44	40	38	36	35	dB/100m

#### Power sum NEXT

Frequency	1	4	10	16	20	31.2	62.5	100	155	200	310	350	MHz
Spec. (Min.) <sup>1)</sup>	-	53.3	47.3	44.3	42.5	39.9	38.4	32.3	29.4	27.8	26.3	24.1	dB/100m
Typical	[71]	62	56	53	52	49	45	42	38	36	34	33	dB/100m

#### Power sum ELFEXT

Frequency	1	4	10	16	20	31.2	62.5	100	155	200	310	350	MHz
Spec. (Min.) <sup>1)</sup>	-	49.0	21.0	36.9	35.0	31.1	25.1	21.0	17.2	15.0	13.0	10.1	dB/100m
Typical	[71]	59	51	46	43	39	33	28	25	23	19	18	dB/100m

#### Power sum ACR

Frequency	1	4	10	16	20	31.2	62.5	100	155	200	310	350	MHz
Spec. (Min.)	-	49	41	36	33	28	21	10	1	-	-	-	dB/100m
Typical	[69]	59	50	45	43	38	29	22	13	8	-	-	dB/100m

#### Return Loss

Frequency	1	4	10	16	20	31.2	62.5	100	155	200	310	350	MHz
Spec. (Min.) <sup>1)</sup>	-	23	25	25	25	23.6	21.5	20.1	18.8	18.0	17.3	17.3	dB/100m
Typical	[31]	33	40	42	42	42	41	41	37	37	35	34	dB/100m

<sup>1)</sup>: Specification values according to cable requirements of ISO/IEC 11801 category 5 enhanced, Sept. 2002.

Note: Values between brackets are for information only

### Ordering information

#### MARKING

Text on the cable jacket      Inkjet printing

**BELDEN DATATWIST® 350 1700ENH UTP CAT5E 4PR AWG24 LSNH  
ISO/IEC 11801 EN50173 -- TESTED TO 350 MHZ --VERIFIED 100 OHM**

Meter marking:                      Yes

#### JACKET COLOUR

<b>Colour</b>	<b>RAL code</b>
Grey	RAL 7032

#### PACKAGING (PUT UP)

305m Unreel Box and 305m, 500m and 1000m Crate Reels