


Shielding and Bonding Cable and Direct Burial Cable

Roadway Loop Cables

Braided Wire



Part No.	Approx. AWG (stranding)	Standard Lengths		Standard Unit Weight		Recommended Current (Amps)	Approximate Circular Area		Nominal ID Tubular		
		Ft.	m	Lbs.	kg		CMA	mm ²	Inch	mm	
Braided Wire											
8660	14.3 (96x34) tinned	50	15.2	.7	.3	27.0	3800	1.92	.125	3.18	
		250	76.2	3.8	1.7						
8668	13.3 (120x34) tinned	50	15.2	1.1	.5	36.0	4800	2.43	.172	4.37	
		250	76.2	5.0	2.3						
8663	11.9 (168x34) tinned	50	15.2	2.1	.9	38.0	6700	3.40	.219	5.56	
		250	76.2	6.8	3.1						
8661	11.3 (192x34) tinned	50	15.2	2.2	1.0	46.0	7600	3.85	.203	5.16	
		250 *	76.2	7.3	3.3						
8669	8.9 (336x34) tinned	50	15.2	3.4	1.5	62.0	13300	6.74	.500	12.70	
		250 *	76.2	11.5	5.2						
8662	6.6 (576x34) tinned	50	15.2	4.7	2.1	80.0	22900	11.60	.781	19.84	
		250 *	76.2	20.0	9.1						
8670	3.4 (480x30) tinned	10	3.0	1.9	.9	145.0	48000	24.32	.750	19.05 (Flat Width)	
		50	15.2	9.0	4.1						
		250 *	76.2	41.3	18.8						

Note: Dimensions shown are approximate, due to pliable nature of braided cables.
*May contain more than one piece. Minimum length of any one piece is 25 ft.


Direct Burial

14 AWG Stranded Conductor (104x34)

Product Description

Tinned copper conductor. Black high-density polyethylene insulation.

Suggested Working Voltage: 600V



Part No.	Insulation Thickness		Jacket Thickness		Nominal OD		Standard Lengths		Standard Unit Weight		Stock Colors
	Inch	mm	Inch	mm	Inch	mm	Ft.	m	Lbs.	kg	
14 AWG Stranded Conductor (104x34)											
80°C											
9438	.032	.81	—	—	.139	3.53	1000	304.8	18.0	8.2	Black