


Data sheet BAT54-F Client - BAT54-F Client

Industrial Ethernet:Industrial Wireless LAN:Chassis:BAT-F:BAT54-F Client	
Name	BAT54-F Client
	
Delivery informations	
Document created at	05-08-2010
Availability	available
Product description	
Description	Dualband Ruggedized Industrial Wireless LAN Access Client with one radio module with IEEE 802.11a/b/g/h/i for installation in harsh environment. (Available Q2/2009)
Port type and quantity	1 x WLAN interface, up to 8 SSIDs per WLAN interface, one LAN port 10/100BASE-TX, autosensing, Power over Ethernet according to IEEE 802.3af
Type	BAT54-F Client
Order No.	943 959-117
Radio technology	
Antenna connector	2 x N-type jack antenna connectors
Range	Up to 20 km with external antenna (depending on type of antenna, frequency range and data rate)
Transmission rate	54 Mbps according to IEEE 802.11g (fallback to 48, 36, 24, 18, 12, 9, 6 Mbps, Automatic Rate Selection), compatible to IEEE 802.11b (11, 5.5, 2, 1 Mbps, Automatic Rate Selection), 802.11 b/g compatibility mode or pure g or pure b selectable. 54 Mbps according to IEEE 802.11a/h (fallback to 48, 36, 24, 18, 12, 9, 6 Mbps, Automatic Rate Selection), Super A/G with Turbo Mode (108 MBps), Bursting, Compression, fully compliant to ETSI requirements with TPC and DFS
Encryption	IEEE 802.11i / WPA2 with passphrase or 802.1x and hardware-accelerated AES, user authentication by 802.1x /EAP, IEEE 802.1x Supplicant in Client Mode, WPA/TKIP, WEP, access-control lists, WLAN port and protocol filter, RADIUS client, built-in firewall with QoS, port filter, protocol filter, PMK-Caching and preauthentication for fast roaming with IEEE 802.1x
Operating system	LAN interface usable for NAT/Reverse NAT (IP-Masquerading) DHCP server, DHCP client, DHCP relay server, DNS server, PPPoE client (incl. Multi-PPPoE), PPTP client and server, NetBIOSProxy, DynDNS client, NTP, Port-Mapping, policy-based routing on basis of routing-tags, tagging according to firewall rules, dynamic routing RIPv2, VRRP, Rapid Spanning Tree Protocol (IEEE 802.1w), ARP, Proxy ARP, BOOTP, DHCP, DNS, HTTP, HTTPS, IP, ICMP, NTP/SNTP, NetBIOS, PPPoE (server), RADIUS, RIP-1, RIP-2, RTP, SIP, SNMP, TCP, TFTP, UDP, VRRP, VLAN with up to 4094 VLAN IDs for WLAN connections, 32 usable simultaneously, dynamic VLAN-tags for 802.1x-clients, integrated RADIUS server with IEEE 802.1x/EAP authentication
Frequency band	1 x radio module, 2.4 GHz and 5 GHz: 2400-2483,5 MHz (ISM) and 5170-5810 MHz
Modulation	22M0F7D(DSSS/OFDM) @ 2.4 GHz 20M0G7D (OFDM) @ 5 GHz
Receiver sensitivity	2.4 GHz 802.11b: -87 dBm @ 11 Mbit/s, -94 dBm @ 1 Mbit/s; 2.4 GHz 802.11g: -87 dBm @ 6 Mbit/s, -70 dBm @ 54 Mbit/s; 5 GHz 802.11a/h: -87 dBm @ 6 Mbit/s, -67 dBm @ 54 Mbit/s
Radio topology	WLAN access client-, client-bridge-modus, fixed mesh with RSTP
Roaming	Soft Roaming, seamless handover between radio cells, IAPP support, IEEE 802.11d support, background scanning for rogue AP detection and fast roaming, support of IEEE 802.11e (WMM), preauthentication and PMK caching with IEEE 802.1x
Radio Power	2.4 GHz 802.11b: +19dBm @ 1 and 2 Mbps, +19dBm @ 5.5 and 11 Mbps, 2.4 GHz 802.11g: +19 dBm @ 6 Mbps, +14 dBm @ 54 Mbps, 5 GHz 802.11a/h: +18 dBm @ 6 Mbps, +12 dBm @ 54 Mbps with TPC and DFS, Power Reduction in 1dB steps down to 0.5 dBm minimum
Power requirements	
Operating voltage	2 x DC 24 V; 1 x Power-over-Ethernet according to IEEE802.3af; all power supplies redundant to each other
Current consumption at 24 V DC	417 mA
Current consumption	DC 24 V: 417 mA; PoE (DC 48 V): 167 mA
Service	
Diagnostics	Extensive LOG and TRACE options, PING and TRACEROUTE for checking connections, LANmonitor status display, internal logging buffer for SYSLOG and firewall events, monitor mode for Ethernet ports, WLANmonitor for WLAN network overview and Rogue AP detection
Management	SNMP management via SNMP V2, private MIB exportable by WEBconfig, MIB II Remote configuration with Telnet/SSL, SSH, browser (HTTP/HTTPS), TFTP or SNMP, firmware upload via HTTP/HTTPS or TFTP Support of up to 4094 VLAN IDs for WLAN connections, 256 simultaneously usable VLAN tags for 802.11 clients
Other services	Warning via e-mail, SNMP-Traps and SYSLOG; Remote management and configuration by modem support via LAN (DSL) or serial port
Ambient conditions	
Operation temperature	-30 °C up to +55 °C
Storage/transport temperature	-40 °C up to +70 °C

Industrial Ethernet:Industrial Wireless LAN:Chassis:BAT-F:BAT54-F Client	
Relative humidity (non-condensing)	max. 95%
MTBF	43.3 years
Mechanical construction	
Dimensions (W x H x D)	261 mm x 189 mm x 55 mm
Mounting	for wall and mast mounting
Protection class	IP 65, IP 67
Approvals	
Safety of information technology equipment	EN 60950
Radio	EN 300328, EN 301893
Environmental	EN 61000-6-2, EN 61131 for operation in automation environment E1 in preparation
Scope of delivery and accessories	
Scope of delivery	Device, CD, M12 connector, 1 x 50 Ohm terminator, mounting material
Accessories to order separately	External antennas for 802.11b/g and 802.11a/h operation adapter cable and surge arrester, mast mount material