


Data sheet BAT54-Rail BG - BAT54-Rail BG

Industrial Ethernet:Industrial Wireless LAN:Chassis:BAT-Rail:BAT54-Rail BG	
Name	BAT54-Rail BG
	
Delivery informations	
Document created at	05-08-2010
Availability	available
Product description	
Description	Single band 2.4 GHz Industrial Wireless LAN Access Point/Client with one radio module with IEEE 802.11b/g/i
Port type and quantity	1 x WLAN interface, up to 8 SSIDs per WLAN interface, one LAN port 10/100BASE-TX, autosensing, Power over Ethernet according to IEEE 802.3af
Type	BAT54-Rail BG
Order No.	943 926-105
Radio technology	
Antenna connector	2 x RP-SMA jack antenna connectors
Range	depending on type of antenna, frequency range and data rate
Transmission rate	54 Mbps according to IEEE 802.11g (fallback to 48, 36, 24, 18, 12, 9, 6 Mbps, Automatic Rate Selection), compatible to IEEE 802.11b (11, 5.5, 2, 1 Mbps, Automatic Rate Selection), 802.11 b/g compatibility mode or pure g or pure b selectable. Super G with Turbo Mode (108 MBps), Bursting, Compression
Encryption	IEEE 802.11i / WPA2 with passphrase or 802.1x and hardware-accelerated AES, user authentication by 802.1x /EAP or LEPS, IEEE 802.1x supplicant in client mode, WPA/TKIP, WEP, access-control lists, WLAN port and protocol filter, RADIUS client and server, built-in firewall with QoS, port filter, protocol filter, IDS and DoS protection, PMK caching and preauthentication for fast roaming with IEEE 802.1x
Operating system	LAN interface usable for simultaneous DSL-over-LAN, IP-Router, NAT/Reverse NAT (IP-Masquerading) DHCP-Server, DHCP-Client, DHCP-Relay-Server, DNS-Server, PPPoE-Client (incl. Multi-PPPoE), PPTP- Client und - Server, NetBIOSProxy, DynDNS-Client, NTP, Port-Mapping, Policy-based Routing on basis of Routing-Tags, Tagging according to firewall rules, dynamic routing RIPv2, VRRP, Rapid Spanning Tree Protocol (IEEE 802.1w), ARP, Proxy ARP, BOOTP, DHCP, DNS, HTTP, HTTPS, IP, ICMP, NTP/SNTP, NetBIOS, PPPoE (Server), RADIUS, RIP- 1, RIP-2, RTP, SIP, SNMP, TCP, TFTP, UDP, VRRP, VLAN with up to 4094 VLAN IDs for WLAN connections, 32 usable simultaneously, dynamic VLAN-Tags for 802.1x-Clients, Integrated RADIUS server with IEEE 802.1x/EAP authentication
Frequency band	1 x radio module, supporting 2.4 GHz: 2400-2483,5 MHz (ISM)
Modulation	22M0F7D(DSSS/OFDM) @ 2.4 GHz
Receiver sensitivity	2.4 GHz 802.11b: -87 dBm @ 11 Mbps, -94 dBm @ 1 Mbps; 2.4 GHz 802.11g: -87 dBm @ 6 Mbps, -70 dBm @ 54 Mbps
Radio topology	WLAN access point, bridge, router, point-to-point, client, client-bridge mode, fixed mesh with RSTP
Roaming	seamless handover between radio cells, IAPP support, IEEE 802.11d support, background scanning for rogue AP detection and fast roaming, support of IEEE 802.11e (WME), preauthentication and PMK caching with IEEE 802.1x
Radio Power	2.4 GHz 802.11b: +19 dBm @1 and 2 Mbps, +19 dBm @ 5.5 and 11 Mbps, 2.4 GHz 802.11g: +19 dBm @ 6 Mbps, +14 dBm @ 54 Mbps, Power Reduction in 1dB steps down to 0.5 dBm minimum
Power requirements	
Operating voltage	2 x DC 24 V; DC 12 V external power supply (230 V) Power over Ethernet according to IEEE802.3af; all power supplies redundant to each other
Current consumption at 24 V DC	417 mA
Current consumption	DC 12 V: 625 mA; DC 24 V: 417 mA; PoE (48 V DC): 167 mA
Service	
Diagnostics	Extensive LOG and TRACE options, PING and TRACEROUTE for checking connections, LANmonitor status display, internal logging buffer for SYSLOG and firewall events, monitor mode for Ethernet ports, WLANmonitor for WLAN network overview and Rogue AP detection
Management	SNMP management via SNMP V2, private MIB exportable by WEBconfig, MIB II; Remote configuration with Telnet/SSL, SSH, browser (HTTP/HTTPS), TFTP or SNMP, firmware upload via HTTP/HTTPS or TFTP; Support of up to 4094 VLAN IDs for WLAN connections, 256 simultaneously usable VLAN tags for 802.11 clients
Other services	Warning via e-mail, SNMP-Traps and SYSLOG; Remote management and configuration by modem support via LAN (DSL) or serial port
Ambient conditions	
Operation temperature	-30 °C to +50 °C
Storage/transport temperature	-40 °C to +70 °C
Relative humidity (non-condensing)	max. 95%

Industrial Ethernet:Industrial Wireless LAN:Chassis:BAT-Rail:BAT54-Rail BG	
MTBF	43.3 years
Mechanical construction	
Dimensions (W x H x D)	80 mm x 100 mm x 135 mm
Mounting	for wall and Din Rail mounting
Protection class	IP 40
Approvals	
Safety of information technology equipment	EN 60950
Radio	EN 300328, notified in all countries of EU. For other notifications or certifications please refer to INET-Sales@hirschmann.de
Environmental	EN 61131, EN 61131 for operation in automation environment
Scope of delivery and accessories	
Scope of delivery	device, CD, serial cable, 2 x 3-dBi-dipol - dualband antennas, 2 x 50 Ohm terminators
Accessories to order separately	external antennas for 802.11b/g operation; adapter cable and surge arrestor