




Data sheet M1-8SM-SC - M1-8SM-SC

Industrial Ethernet:Workgroup Switches:Media modules:M1-8SM-SC

Name	M1-8SM-SC
	
Delivery informations	
Document created at	09-08-2010
Availability	available
Product description	
Description	Media module for modular, managed, Industrial Workgroup Switch MACH100 100 BASE-FX Singlemode
Type	M1-8SM-SC
Order No.	943 970-201
Network size - length of cable	
Twisted pair (TP)	0 - 100m
Multimode fiber (MM) 50/125 µm	-
Multimode fiber (MM) 62.5/125 µm	-
Single mode fiber (SM) 9/125 µm	0 - 32,5 km, 16 dB Link Budget at 1300 nm, A = 0,4 dB/km, 3 dB Reserve, D = 3,5 ps/(nm x km)
Single mode fiber (LH) 9/125 µm (long haul transceiver)	-
Power requirements	
Power consumption	10 W
Ambient conditions	
Operating temperature	0° - +50°C
Storage/transport temperature	-20° - +85°C
Relative humidity (non-condensing)	10% to 95%
MTBF	72.54 years (MIL-HDBK-217F Gb 25°C)
Mechanical construction	
Dimensions (W x H x D)	138 x 90 x 42
Mounting	Media Module
Weight	0.18 kg
Protection class	IP20
EMC interference immunity	
EN 61000-4-2 electrostatic discharge (ESD)	4 kV contact discharge, 8 kV air discharge
EN 61000-4-3 electromagnetic field	10 V/m (80 - 2700 MHz)
EN 61000-4-4 fast transients (burst)	2 kV power line, 4 kV data line
EN 61000-4-5 surge voltage	power line: 2 kV (line/earth), 1 kV (line/line), 4 kV data line
EN 61000-4-6 conducted immunity	10 V (150 kHz - 80 MHz)
EMC emitted immunity	
FCC CFR47 Part 15	FCC 47 CFR Part 15 Class A
EN 55022	EN 55022 Class A
Approvals	
Safety of industrial control equipment	cUL 508 (pending)
Scope of delivery and accessories	
Scope of delivery	Media module, user manual