



## Data sheet MACH1000, 16 ports Full Gigabit Ethernet PoE switch - ports on rear - MAR1142-4C4C4C4C9999SLLHPPH05.0.

Industrial Ethernet:Ruggedized Switches:Fast/Gigabit Ethernet Control Cabinet Switches:PoE Control Cabinet Switches:MACH1000, 16 ports Full Gigabit Ethernet PoE switch - ports on rear

<b>Name</b>		MACH1000, 16 ports Full Gigabit Ethernet PoE switch - ports on rear
		
<b>Delivery informations</b>		
Document created at	09-08-2010	
Availability	available	
<b>Product description</b>		
Description	Ethernet/Fast Ethernet/Gigabit Ethernet switch, Power over Ethernet 4 ports, managed, Industrial Switch 19" rack mount, ports on rear, fanless design	
Port type and quantity	16 x combo ports (10/100/1000BASE TX RJ45 plus related FE/GE-SFP slot)	
Type	MAR1142-4C4C4C4C9999SLLHPPH05.0.	
Order No.	MAR1142-4C4C4C4C9999SLLHPPH05.0.	
<b>More Interfaces</b>		
Power supply/signaling contact	power supply 1: power supply, 2 pin plug-in terminal block, signal contact, 2 pin plug-in terminal block; power supply 2: power supply, 2 pin plug-in terminal block, signal contact, 2 pin plug-in terminal block	
V.24 interface	1 x RJ11 socket	
USB interface	1 x USB to connect the AutoConfiguration Adapter ACA21-USB	
<b>Network size - length of cable</b>		
Twisted pair (TP)	0 m - 100 m	
Multimode fiber (MM) 50/125 µm	cf. Gigabit and Fast Ethernet SFP modules	
Multimode fiber (MM) 62.5/125 µm	cf. Gigabit and Fast Ethernet SFP modules	
Single mode fiber (SM) 9/125 µm	cf. Gigabit and Fast Ethernet SFP modules	
Single mode fiber (LH) 9/125 µm (long haul transceiver)	cf. Gigabit and Fast Ethernet SFP modules	
<b>Network size - cascading</b>		
Line - / star topology	any	
Ring structure (HIPER-Ring) quantity switches	up to 10 ms (10 switches), up to 30 ms (50 switches), up to 40 ms (100 switches), up to 60 ms (200 switches)	
<b>Power requirements</b>		
Operating voltage	power supply 1: 24/36/48 V DC, power supply 2: 24/36/48 V DC	
Current consumption at 24 V DC	power supply 1: 1080 mA max., if all ports are equipped with SFP; power supply 2: 1080 mA max., if all ports are equipped with SFP	
Current consumption at 230 V AC	power supply 1: n/a; power supply 2: n/a	
Power output in Btu (IT) h	90 max (350 PoE option)	
<b>Software</b>		
Management	Serial interface, web-interface, SNMP V1/V2, HiVision file transfer SW HTTP/TFTP	
Diagnostics	LEDs, log-file, syslog, signal contact, RMON, port mirroring, topology discovery 802.1AB, cable diagnostic (TX), disable learning	
Configuration	Command line interface (CLI), TELNET, BootP, DHCP, DHCP option 82, HiDiscovery, auto-configuration adapter (ACA21-USB), DHCP server per port	
Security	Port Security (IP und MAC), SNMP V3, SSH, Authentication (802.1x), Radius Authentication for SNMPv3 (Web)	
Redundancy functions	HIPER-Ring, Fast HIPER-Ring, MRP (IEC-ring functionality), RSTP 802.1w, MRP and RSTP in parallel, link aggregation, multiple rings	
Filter	QoS 4 classes, prioritisation (IEEE 802.1D/p), VLAN (IEEE 802.1Q), multicast (IGMP snooping/querier), multicast detection unknown multicast, broadcast-, unicast-, multicast limiter, fast aging, GMRP IEEE 802.1D	
Industrial Profiles	EtherNet/IP and PROFINET (2.2 PDEV, GSDML Stand-alone generator, automatic device exchange) profiles included, configuration and diagnostic via automation software tools like e.g. STEP7, or Control Logix	
Time synchronisation	SNTP Server, PTP / IEEE 1588, realtime clock with energy buffer	
Flow control	Flow Control 802.3x, Port Priority 802.1D/p, Priority (TOS/DIFFSERV), Prio (MAC/IP), Prio Mapping (TOS Layer2), Traffic Shaping (Unicast, Multicast, Broadcast) Ingress / Egress	
<b>Ambient conditions</b>		
Operating temperature	0 °C - 60 °C	
Storage/transport temperature	-40 °C - 85 °C	



**Industrial Ethernet:Ruggedized Switches:Fast/Gigabit Ethernet Control Cabinet Switches:PoE Control Cabinet Switches:MACH1000, 16 ports Full Gigabit Ethernet PoE switch - ports on rear**

Relative humidity (non-condensing)	5 % - 95 %
MTBF	119540
Protective paint on PCB	No
<b>Mechanical construction</b>	
Dimensions (W x H x D)	445 mm x 44 mm x 345 mm
Mounting	19" control cabinet
Weight	5600 gram
Protection class	IP30
<b>Mechanical stability</b>	
IEC 60068-2-27 shock	15 g, 11 ms duration, 18 shocks
IEC 60068-2-6 vibration	1 mm, 2 Hz-13.2 Hz, 90 min.; 0.7g, 13.2 Hz-100 Hz, 90 min.; 3.5 mm, 3 Hz-9 Hz, 10 cycles, 1 octave/min.; 1 g, 9 Hz-150 Hz, 10 cycles, 1 octave/min.
<b>EMC interference immunity</b>	
EN 61000-4-2 electrostatic discharge (ESD)	8 kV contact discharge, 15 kV air discharge
EN 61000-4-3 electromagnetic field	35 V/m (80-2700 MHz); 1 kHz, 80% AM
EN 61000-4-4 fast transients (burst)	4 kV power line, 4 kV data line
EN 61000-4-5 surge voltage	power line: 2 kV (line/earth), 1 kV (line/line), 1 kV data line IEEE1613; power line 5 kV (line/earth)
EN 61000-4-6 conducted immunity	30 V, 50 Hz continuous; 300 V, 50 Hz 1 s
EN 61000-4-16 mains frequency voltage	30 V, 50 Hz continuous; 300 V, 50 Hz 1 s
<b>EMC emitted immunity</b>	
FCC CFR47 Part 15	FCC 47 CFR Part 15 Class A
EN 55022	EN 55022 Class A
<b>Approvals</b>	
Safety of industrial control equipment	cUL 508 (pending)
Hazardous locations	cUL 1604 Class1 Div 2 (pending)
Shipbuilding	Germanischer Lloyd (pending)
Railway norm	EN 50121-4, EN50155 (pending), NEMA TS
Substation	IEC 61850-3, IEEE 1613
Transportation	EN 50121-4, EN50155 (pending), NEMA TS
<b>Scope of delivery and accessories</b>	
Scope of delivery	device, operating manual