

## Data sheet

### OCTOPUS 16M-8PoE-2FX - OCTOPUS 16M-8PoE-2FX

Industrial Ethernet:IP67 Switches:Managed IP67 Switches:Fast Ethernet PoE Switches:OCTOPUS 16M-8PoE-2FX

<b>Name</b>	OCTOPUS 16M-8PoE-2FX
	
<b>Delivery informations</b>	
<b>Document created at</b>	06-08-2010
<b>Availability</b>	available
<b>Product description</b>	
<b>Description</b>	Managed IP 67 switch in accordance with IEEE 802.3, store-and-forward-switching, software layer 2 professional, Ethernet (10 Mbit/s) and Fast-Ethernet (100 Mbit/s), power sourcing equipment according to IEEE 802.3af (inline power)
<b>Port type and quantity</b>	8 x 10/100 BASE-TX PoE (phantom power) plus 6 x 10/100 BASE-TX, M12 D coding, 4-pole, TP cable, auto-crossing, auto-negotiation, auto-polarity, 2 x 100Base-FX MM, microFX
<b>Type</b>	OCTOPUS 16M-8PoE-2FX
<b>Order No.</b>	943 960-101
<b>More Interfaces</b>	
<b>Power supply/signaling contact</b>	1 x M12 5-pin connector, A coding
<b>V.24 interface</b>	1 x M12 4-pin socket, A coding
<b>USB interface</b>	1 x M12 5-pin socket, A coding
<b>Network size - length of cable</b>	
<b>Twisted pair (TP)</b>	0 - 100 m
<b>Multimode fiber (MM) 50/125 µm</b>	0 - 5000 m, 8 dB Link Budget at 1300 nm, A = 1 dB/km, 3 dB Reserve, B = 800 MHz x km
<b>Multimode fiber (MM) 62.5/125 µm</b>	0 - 4000 m, 11 dB Link Budget at 1300 nm, A = 1 dB/km, 3 dB Reserve, B = 500 MHz x km
<b>Network size - cascading</b>	
<b>Line - / star topology</b>	Any
<b>Ring structure (HIPER-Ring) quantity switches</b>	50 (reconfiguration time < 0.3 sec.)
<b>Power requirements</b>	
<b>Operating voltage</b>	DC 46 V to 58 V
<b>Power consumption</b>	max. 142 W
<b>Current consumption at 24 V DC</b>	n/a
<b>Current consumption at 48 V DC</b>	0.35 A (no PD), max. 3.2 A (8 PD Class 0)
<b>Service</b>	
<b>Management</b>	Serial interface, Web interface, SNMP V1/V2/V3 (HiVision/Industrial HiVision)
<b>Diagnostics</b>	LEDs (power 1, power 2, link status, data, redundancy manager, error) cable tester, signalling contact, RMON (statistics, history, alarms, events), SysLog support, port mirroring
<b>Configuration</b>	Command Line Interface (CLI scripting), auto-configuration adapter (ACA21-M12), TELNET, BootP, DHCP Option 82, HiDiscovery
<b>Security</b>	Port security (MAC and IP address), SNMPv3, SSHv3, SNMP access settings (VLAN/IP), IEEE 802.1X authentication
<b>Other services</b>	4 QoS queues, user priority (IEEE 802.1D/p), VLAN (IEEE 802.1Q), unknown multicast filtering, multicast support (IGMP Snooping/Querier, GMRP), broadcast limiter per port, ingress and egress packet limiter, Flow Control IEEE 802.3x, LLDP (topology discovery IEEE 802.1AB), Link Aggregation (IEEE 802.3ad), buffered real-time clock, PTP support (Precision Time Protocol) (IEEE 1588 client for system clock only), SNTP support (Simple Network Time Protocol, client/server)
<b>Redundancy</b>	
<b>Redundancy functions</b>	HIPER-Ring (ring structure), RSTP (Rapid Spanning Tree Protocol, IEEE 802.1w), redundant network/ring coupling, redundant power supply
<b>Ambient conditions</b>	
<b>Operating temperature</b>	-40 °C to +70 °C
<b>Storage/transport temperature</b>	-40 °C to +85 °C
<b>MTBF</b>	20,7 Jahre; Telecordia SR-332: Gb 25 °C
<b>Relative humidity</b>	10 to 100% (also condensing)

Industrial Ethernet:IP67 Switches:Managed IP67 Switches:Fast Ethernet PoE Switches:OCTOPUS 16M-8PoE-2FX	
<b>Mechanical construction</b>	
Dimensions (W x H x D)	261 mm x 189 mm x 70 mm
Mounting	Wall mounting
Weight	1950 g
Protection class	IP 67
<b>Mechanical stability</b>	
IEC 60068-2-27 shock	15 g, 11 ms duration, 18 shocks
IEC 60068-2-6 vibration	1 mm, 2 Hz - 13.2 Hz, 90 min.; 0,7g, 13.2 Hz - 100 Hz, 90 min.; 3.5 mm, 3 Hz - 9 Hz, 10 cycles, 1 octave/min.; 1g, 9 Hz - 150 Hz, 10 cycles, 1 octave/min.
<b>EMC interference immunity</b>	
EN 61000-4-2 electrostatic discharge (ESD)	6 kV contact discharge, 8 kV air discharge
EN 61000-4-3 electromagnetic field	20 V/m (80 - 1000 MHz)
EN 61000-4-4 fast transients (burst)	4 kV power line, 4 kV data line
EN 61000-4-5 surge voltage	power line: 2 kV (line/earth), 1 kV (line/line), 1 kV data line
EN 61000-4-6 conducted immunity	3 V (10 kHz - 150 kHz), 10 V (150 kHz - 80 MHz)
<b>EMC emitted immunity</b>	
FCC CFR47 Part 15	FCC CFR47 Part 15 Class A
EN 55022	EN 55022 Class A
<b>Approvals</b>	
Safety of industrial control equipment	cUL 508 pending
Germanischer Lloyd	n/a
Employment in vehicles	n/a
Electronic mechanisms on rail-mounted vehicles	n/a
<b>Scope of delivery and accessories</b>	
Scope of delivery	covers for sealing unused ports, M12-connector (ELWIK A 5012 PG7) for power connection, description and operating instructions
Accessories to order separately	Auto Configuration Adapter (ACA21-M12), order no. 943 931-001; modem cable (OCTOPUS Terminalkabel), order no. 943 902-001; field assembleable M12-connector (EM12S OCTOPUS), order no. 934 445-001; patchcords (EM12S 001Lxxxx OCTOPUS), order no. 934 578-xxx; crossing M12 to RJ45 (EF12RJ45 OCTOPUS), order no. 934 498-001
Note	Please note that some recommended accessory parts only support a temperature range from -25 °C to +70 °C and might limit the possible operating conditions for the entire system. Specially designed connector types with protection class IP 67 and extended temperature range are available on request. Furthermore unsealed accessories like RJ45 adapters or terminal access cables are certainly not suitable inside IP 67 areas.