



7795A Coax - Brilliance® VideoFlex® Snake Cable - Bundled

	<p>For more information please call 1-800-Belden1</p> <p><u>See Put-ups and Colors</u></p>
---	---

Description:

RGB coaxial cable, 4 coaxes. Each coax 20 AWG solid bare copper, gas-injected foam HDPE core, Duofoil® + 95% tinned copper braid, PVC jacket; overall PVC jacket.

PHYSICAL CHARACTERISTICS:

CONDUCTOR:

Number of Coax	4
Total Number of Conductors	4
RG Type	59/U
AWG	20
Stranding	Solid
Conductor Diameter	.032 in.
Conductor Material	BC - Bare Copper

INSULATION:

Insulation Material	Gas-injected FHDPE - Foam High Density Polyethylene
Insulation Diameter	.145 in.

INNER SHIELD:

Inner Shield Material Trade Name	Duofoil®
Inner Shield Type	Tape/Braid

Inner Shield Material :

Layer Number	Trade Name	Type	Material	% Coverage (%)
1	Duofoil®	Tape	Aluminum Foil-Polyester Tape-Aluminum Foil	100
2		Braid	TC - Tinned Copper	95

Inner Shield %Coverage	100 %
------------------------	-------

INNER JACKET:

Inner Jacket Material	PVC - Polyvinyl Chloride
Inner Jacket Diameter	.235 in.

Inner Jacket Color Code Chart :



7795A Coax - Brilliance® VideoFlex® Snake Cable - Bundled

Number	Color
1	Red
2	Green
3	Blue
4	White

OUTER JACKET:

Outer Jacket Material	PVC - Polyvinyl Chloride
-----------------------	--------------------------

OVERALL NOMINAL DIAMETER:

Overall Nominal Diameter	.706 in.
--------------------------	----------

MECHANICAL CHARACTERISTICS:

Operating Temperature Range	-35°C To +75°C
UL Temperature Rating	60°C
Non-UL Temperature Rating	75°C
Bulk Cable Weight	190 lbs/1000 ft.
Max. Recommended Pulling Tension	288 lbs.
Min. Bend Radius (Install)	7 in.

APPLICABLE SPECIFICATIONS AND AGENCY COMPLIANCE:

APPLICABLE STANDARDS:

NEC/(UL) Specification	CMR
CEC/C(UL) Specification	CMG

FLAME TEST:

UL Flame Test	UL1666 Vertical Shaft
---------------	-----------------------

SWEEP TEST:

Sweep Testing	Sweep tested 5 MHz to 3 GHz.
---------------	------------------------------

SUITABILITY:

Suitability - Indoor	Yes
Suitability - Outdoor	Yes
Suggested Connectors	Kings 2065-2-9 75 Ohm BNC, each coax

PLENUM/NON-PLENUM:

Plenum (Y/N)	N
--------------	---

ELECTRICAL CHARACTERISTICS:

Nom. Characteristic Impedance	75 Ohms
Nom. Inductance	0.107 µH/ft
Nom. Capacitance Conductor to Shield	16.2 pF/ft
Nominal Velocity of Propagation	83 %



7795A Coax - Brilliance® VideoFlex® Snake Cable - Bundled

Nominal Delay	1.22 ns/ft
Nom. Conductor DC Resistance @ 20 Deg. C	10.0 Ohms/1000 ft
Nom. Inner Shield DC Resistance:	3.8 Ohms/1000 ft

Minimum Return Loss :

Description	Frequency (MHz)	Start Frequency (MHz)	Stop Frequency (MHz)	Minimum Return Loss (dB)
		5	850	23
		851	3000	15

Nom. Attenuation :

Description	Frequency (MHz)	Start Frequency (MHz)	Stop Frequency (MHz)	Nom. Attenuation (dB/100 ft.)
	1			0.3
	3.6			0.6
	10			0.9
	71.5			2.1
	135			2.7
	270			3.8
	360			4.4
	540			5.5
	720			6.4
	750			6.5
	1000			7.6
	1500			9.4
	2500			12.4
	3000			13.8

Max. Operating Voltage - UL	300 V RMS
Other Electrical Characteristic 1	Impedance tested in accordance with ASTM D-4566 paragraph 43.2, option 2 using a 75 Ohm fixed bridge and termination.
Other Electrical Characteristic 2	Return Loss Tested in Accordance With ASTM D-4566 Paragraph 45.3, Using a 75 Ohm Fixed Bridge and Termination.

PUT-UPS AND COLORS:

Item	Description	Put-Up (ft.)	Ship Weight (lbs.)	Jacket Color	Notes
7795A B591000	4 #20 PE/GIFHDPE SH FRPVC PVC	1000	237	BLACK, MATTE	C
7795A B59500	4 #20 PE/GIFHDPE SH FRPVC PVC	500	116.5	BLACK, MATTE	C

C = CRATE REEL PUT-UP.

Revision Number: 2 Revision Date: 09-24-2004



7795A Coax - Brilliance® VideoFlex® Snake Cable - Bundled

© 2003 Belden Wire & Cable Company
All Rights Reserved.

Although Belden Electronics Division ("Belden") makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability. Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein. All sales of Belden products are subject to Belden's standard terms and conditions of sale.