

3084A Paired - DeviceBus® for ODVA DeviceNet™

	<p>For more information please call 1-800-Belden1</p> <p><u>See Put-ups and Colors</u></p>
---	---

Description:

300V Class 2 Thin, 22 and 24 AWG stranded tinned copper conductors, PVC insulation (power), FRFPE insulation (Data), 100% individually foil shielded and an overall 65% tinned copper braid, drain wire, sunlight/oil-resistant PVC jacket.

PHYSICAL CHARACTERISTICS:

CONDUCTOR:

Number of Pairs	2
Number of Conductors	4

AWG :

Number of Pairs	AWG	Stranding	Conductor Material	Conductor Diameter (in.)
1	22	19x34	TC - Tinned Copper	
1	24	19x36	TC - Tinned Copper	

Stranding	19x34, 19x36
Conductor Material	TC - Tinned Copper

INSULATION:

Insulation Material	PVC - Polyvinyl Chloride, FRFPE - Flame Retardant Foam Polyethylene
---------------------	---

Insulation Material (Multi-AWG) :

AWG	Layer Number	Material Trade Name	Material	Wall Thickness (in.)	Diameter (in.)
22			PVC - Polyvinyl Chloride		
24			FRFPE - Flame Retardant Foam Polyethylene		

PAIR:

Pair Shield Type	Tape/Tape
------------------	-----------

Pair Shield Material :

Description	Material Trade Name	Type	Material	% Coverage (%)	Stranding	Diameter (in.)	Conductor Material
22 AWG Pair		Tape	Aluminum Foil-Polyester Tape	100			
24 AWG Pair		Tape	Aluminum Foil-Polyester Tape	100			

Pair Shield % Coverage	100 %
------------------------	-------

PAIR SHIELD DRAIN WIRE :

Pair Shield Drain Wire AWG	22
----------------------------	----



3084A Paired - DeviceBus® for ODVA DeviceNet™

Pair Shield Drain Wire Stranding	19x34
Pair Shield Drain Wire Conductor Material	TC - Tinned Copper

Pair Color Code Chart :

Number	Color	Number	Color
22 AWG Pair	Red & Black	24 AWG Pair	Blue & White

OUTER SHIELD:

Outer Shield Type	Braid
Outer Shield Material	TC - Tinned Copper
Outer Shield % Coverage	65 %

OUTER JACKET:

Outer Jacket Material	PVC - Polyvinyl Chloride
-----------------------	--------------------------

OVERALL NOMINAL DIAMETER:

Overall Nominal Diameter	.280 in.
--------------------------	----------

MECHANICAL CHARACTERISTICS:

Operating Temperature Range	-20°C To +75°C
UL Temperature Rating	75°C
Bulk Cable Weight	41 lbs/1000 ft.
Max. Recommended Pulling Tension	65 lbs.
Min. Bend Radius (Install)	2.75 in.

APPLICABLE SPECIFICATIONS AND AGENCY COMPLIANCE:

APPLICABLE STANDARDS:

NEC/(UL) Specification	CMG, CL2
CEC/C(UL) Specification	CMG
AWM Specification	I/II A

FLAME TEST:

UL Flame Test	UL1581 Vertical Tray
CSA Flame Test	FT4

SUITABILITY:

Sunlight Resistance	Yes
Oil Resistance	Yes

ELECTRICAL CHARACTERISTICS:

Nom. Characteristic Impedance :

Description	Nom. Characteristic Impedance (Ohms)
24 AWG Pair	120

Nom. Inductance :

3084A Paired - DeviceBus® for ODVA DeviceNet™

Description	Nom. Inductance (μH/ft)
22 AWG Pair	.221
24 AWG Pair	.251

Nom. Capacitance Conductor to Conductor @ 1 KHz 24 AWG pair 12.0 pF/ft

Nom. Capacitance Conductor to Conductor :

Description	Frequency (kHz)	Start Frequency (kHz)	Stop Frequency (kHz)	Nom. Capacitance Conductor to Conductor (pF/ft)
24 AWG Pair	1			12.0

Nominal Velocity of Propagation :

Description	Nominal Velocity of Propagation (%)
24 AWG Pair	75

Maximum Delay :

Description	Frequency (MHz)	Start Frequency (MHz)	Stop Frequency (MHz)	Maximum Delay (ns/ft)
24 AWG Pair				1.36

Maximum Conductor DC Resistance :

Description	Maximum Conductor DC Resistance @ 20 Deg. C (Ohms/1000 ft)
22 AWG	17.5
24 AWG	28.0

Nominal Outer Shield DC Resistance @ 20 Deg. C 3.2 Ohms/1000 ft

Max. Attenuation (dB/100 ft.) :

Description	Frequency (MHz)	Start Frequency (MHz)	Stop Frequency (MHz)	Max. Attenuation (dB/100 ft.)
24 AWG Pair Only	.125			.29
	.500			.50
	1.000			.70

Max. Operating Voltage - UL :

UL Voltage	UL
300 V RMS	CL2, CMG
300 V RMS	C(UL) AWM
600 V RMS	UL AWM

Other Maximum Currents 2.4 Amps per conductor @ 25°C (22 AWG), 1.7 Amps per conductor @ 25°C (24 AWG)

NOTES:

Notes Flex Life: +/- 90 Degree Flex Test, 2" Diameter, 2 lbs. tension: 2000 Cycles minimum. Meter marks on jacket to aid users in installation.

PUT-UPS AND COLORS:

Item	Description	Put-Up (ft.)	Ship Weight (lbs.)	Jacket Color	Notes
3084A T5U1000	2 #22, 2 #24 SHLD PVC	1000	49	GRAY T5U	C Z
3084A T5U2000	2 #22, 2 #24 SHLD PVC	2000	100	GRAY T5U	C



3084A Paired - DeviceBus® for ODVA DeviceNet™

3084A T5U500	2 #22, 2 #24 SHLD PVC	500	26	GRAY T5U	C Z
--------------	--------------------------	-----	----	----------	-----

C = CRATE REEL PUT-UP.

Z = FINAL PUT-UP LENGTH MAY VARY (+ OR -) 10% FOR SPOOLS OR REELS AND (+ OR -) 5% FOR UNREEL CARTONS FROM LENGTH SHOWN.

Revision Number: 1 Revision Date: 02-24-2004

© 2003 Belden Wire & Cable Company
All Rights Reserved.

Although Belden Electronics Division ("Belden") makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.