

8477 Paired - Audio, Control and Instrumentation Cable

	<p>For more information please call 1-800-Belden1</p> <p><u>See Put-ups and Colors</u></p> <p>Color Code Chart : No. 1.pdf</p>
---	---

Description:

12 AWG stranded (65x30) tinned copper conductors, twisted pair, PVC insulation, PVC jacket.

PHYSICAL CHARACTERISTICS:

CONDUCTOR:

Number of Pairs	1
Total Number of Conductors	2
AWG	12
Stranding	65x30
Conductor Material	TC - Tinned Copper

INSULATION:

Insulation Material	PVC - Polyvinyl Chloride
Nom. Insulation Wall Thickness	.032 in.
Lay Length	2.4 in.
Twists/ft.	4.9

Pair Color Code Chart :

Number	Color
1	Black & White

OUTER SHIELD:

Outer Shield Material	Unshielded
-----------------------	------------

OUTER JACKET:

Outer Jacket Material	PVC - Polyvinyl Chloride
Outer Jacket Nominal Wall Thickness	.035 in.

OVERALL NOMINAL DIAMETER:

Overall Nominal Diameter	.386 in.
--------------------------	----------

MECHANICAL CHARACTERISTICS:

Operating Temperature Range	-20°C To +90°C
Non-UL Temperature Rating	90°C (UL AWM Style 2587)
Bulk Cable Weight	77 lbs/1000 ft.

8477 Paired - Audio, Control and Instrumentation Cable

Max. Recommended Pulling Tension	150 lbs.
Min. Bend Radius (Install)	7.7 in.

APPLICABLE SPECIFICATIONS AND AGENCY COMPLIANCE:

APPLICABLE STANDARDS:

NEC/(UL) Specification	CL3R
AWM Specification	UL Style 2587 (600 V 90°C)

FLAME TEST:

UL Flame Test	UL1581 Vertical Tray
---------------	----------------------

PLENUM/NON-PLENUM:

Plenum (Y/N)	N
--------------	---

ELECTRICAL CHARACTERISTICS:

Nom. Inductance	0.18 μ H/ft
Nom. Capacitance Conductor to Conductor @ 1 KHz	35 pF/ft
Nom. Capacitance Conductor to Conductor @ 1 KHz	35 pF/ft
Nom. Conductor DC Resistance @ 20 Deg. C	1.8 Ohms/1000 ft

Max. Operating Voltage - UL :

UL Voltage	UL
300 V RMS	CL3R
600 V RMS	UL AWM Style 2587

Max. Recommended Current	13 Amps per conductor @ 25°C
--------------------------	------------------------------

NOTES:

Notes	See NEC Guidelines for applicable CL3 voltage ratings.
-------	--

PUT-UPS AND COLORS:

Item	Description	Put-Up (ft.)	Ship Weight (lbs.)	Jacket Color	Notes
8477 0601000	2 #12 PVC FRPVC	1000	85	CHROME	C
8477 060500	2 #12 PVC FRPVC	500	43.5	CHROME	C
8477 060U500	2 #12 PVC FRPVC	U500	43	CHROME	

C = CRATE REEL PUT-UP.

Revision Number: 1 Revision Date: 09-21-2004

8477 Paired - Audio, Control and Instrumentation Cable

© 2003 Belden Wire & Cable Company
All Rights Reserved.

Although Belden Electronics Division ("Belden") makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.