



**9368 Paired - 300V Power-Limited Tray Cable**

	<p><b>For more information please call</b> <b>1-800-Belden1</b></p> <p><u>See Put-ups and Colors</u></p> <p><b>Color Code Chart : ICEA Table E2.pdf</b></p>
--	---

**Description:**

18 AWG pairs stranded (19x30) tinned copper conductors, twisted pairs, PVC insulation, individually shielded (100% coverage), PVC jacket.

**PHYSICAL CHARACTERISTICS:**

**CONDUCTOR:**

Number of Pairs	2
Total Number of Conductors	4
AWG	18
Stranding	19x30
Conductor Material	TC - Tinned Copper

**INSULATION:**

Insulation Material	PVC - Polyvinyl Chloride
---------------------	--------------------------

Pair Color Code Chart :

Number	Color	Number	Color
1	Black & Red #1	2	Black & Red #2

**INNER SHIELD:**

Inner Shield Material Trade Name	Beldfoil®
Inner Shield Type	Tape
Inner Shield Material	Aluminum Foil-Polyester Tape
Inner Shield % Coverage	100 %
Inner Shield Drain Wire AWG	20
Inner Shield Drain Wire Stranding	7x30
Inner Shield Drain Wire Conductor Material	TC - Tinned Copper

**OVERALL CABLING:**

Overall Cabling Direction	Left-hand Lay
---------------------------	---------------

**OUTER SHIELD:**

Outer Shield Material	Unshielded
-----------------------	------------



**9368 Paired - 300V Power-Limited Tray Cable**

**OUTER JACKET:**

Outer Jacket Material	PVC - Polyvinyl Chloride
Outer Jacket Nominal Wall Thickness	.042 in.
Outer Jacket Ripcord	Yes

**OVERALL NOMINAL DIAMETER:**

Overall Nominal Diameter	.378 in.
--------------------------	----------

**MECHANICAL CHARACTERISTICS:**

Operating Temperature Range	-30°C To +105°C
UL Temperature Rating	105°C
Bulk Cable Weight	69 lbs/1000 ft.
Max. Recommended Pulling Tension	125 lbs.
Min. Bend Radius (Install)	3.75 in.

**APPLICABLE SPECIFICATIONS AND AGENCY COMPLIANCE:**

**APPLICABLE STANDARDS:**

NEC/(UL) Specification	PLTC, ITC, CMG
CEC/C(UL) Specification	CMG
EU CE Mark (Y/N)	Yes
EU RoHS Compliant (Y/N)	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	04/01/2005

**FLAME TEST:**

UL Flame Test	UL1685 FT4 Loading
C(UL) Flame Test	FT4
IEEE Flame Test	1202
ICEA Flame Test	T-29-520

**SUITABILITY:**

Suitability - Indoor	Yes
Suitability - Outdoor	Yes
Suitability - Burial	Yes
Sunlight Resistance	Yes

**PLENUM/NON-PLENUM:**

Plenum (Y/N)	N
--------------	---

**ELECTRICAL CHARACTERISTICS:**

Nom. Inductance	.18 µH/ft
Nom. Capacitance Conductor to Shield @ 1 KHz	102 pF/ft
Nom. Capacitance Conductor to Conductor @ 1 KHz	57 pF/ft



**9368 Paired - 300V Power-Limited Tray Cable**

Nom. Conductor DC Resistance @ 20 Deg. C	5.96 Ohms/1000 ft
Ind. Pair Nominal Shield DC Resistance @ 20 Deg. C	8.3 Ohms/1000 ft
Max. Operating Voltage - UL	300 V RMS (PLTC, CMG), 150 V RMS (ITC)
Max. Recommended Current	6.4 Amps per conductor @ 25°C

**PUT-UPS AND COLORS:**

Item	Description	Put-Up (ft.)	Ship Weight (lbs.)	Jacket Color	Notes
9368 0601000	2 PR #18 PVC SH PVC	1000	73	CHROME	C
9368 060500	2 PR #18 PVC SH PVC	500	37.5	CHROME	C

C = CRATE REEL PUT-UP.

Revision Number: 1      Revision Date: 09-23-2005

© 2005 Belden Wire & Cable Company  
All Rights Reserved.

Although Belden Electronics Division ("Belden") makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden CDT Electronics Division believes this product to be in compliance with the following environmental regulations: California Proposition 65 Consent Judgment For Wire & Cable Mfgs.(San Francisco Superior Court Nos. 312962 And 320342); EU RoHS (Directive 2002/95/EC, 27-Jan-2003);Material manufactured prior to the compliance date may still be in stock at Belden facilities and in our Distributor's inventory. EU ELV (Directive 2000/53/EC, 18-Sept-2000); EU WEEE (Directive 2002/96/EC, 27-Jan-2003); And EU BFR (Directive 2003/11/EC, 6-Feb-2003). The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information and belief at the date of its publication. The information provided in the Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden CDT Electronics Division declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.