



**Application**

- Horizontal Patch Cable
- Support current **Category 5e** applications, such as: 10 Base-T, 100 Base-T, FDDI, ATM

**Standards**

- General standards: **ISO/IEC 11801, EN 50173, TIA/EIA 568-B.2**

**Construction & Dimensions**

- Construction: shielded 4 twisted pairs
- Conductor: stranded bare copper (7 x 0.16 mm)
- Conductor diameter: AWG 26 (0,48 mm)
- Conductor insulation material: Foam skin Polyethylene (PE)
- Diameter over insulation: 0,98mm ± 0.05 mm
- Drainwire: Tinned copper, 7 x 0.16 mm
- Shield: Aluminium/polyester foil
- Jacket material: FRNC (Flame retardant)
- Outer diameter: 5.2 mm ± 0.2 mm

**Electrical characteristics (at 20 °C)**

**Attenuation**

Frequency	1	4	10	16	20	31.25	62.5	100	MHz
Spec. (Max.) <sup>1)</sup>	0,3	0,6	1,0	1,2	1,4	1,8	2,6	3,3	dB/10m

**NEXT (Near end crosstalk)**

Frequency	1	4	10	16	20	31.25	62.5	100	MHz
Spec. (Min.) <sup>1)</sup>	62	53	47	44	42	40	35	32	dB

**ACR**

Frequency	1	4	10	16	20	31.25	62.5	100	MHz
Spec. (Min.) <sup>1)</sup>	62	52	46	43	41	38	32	29	dB/10m

<sup>1)</sup>: Specification values according to cable requirements of ISO/IEC 11801

**Electrical characteristics (at 20 °C)**

Nominal mutual capacitance at 1 kHz	50 nF/km
Maximum conductor DCR	135 Ohm/km
NVP - Nominal Velocity of Propagation	0.75 c
SKEW – Propagation delay difference (100 MHz)	typical ≤ 40 ns/100m
Impedance 1 - 100 MHz	100 ± 15 Ohm

**Product Datasheet**

P/N - 43055 Rev. 1

Page 2 of 2

Date 16-02-2004

**Belden 1868ENH****FLEX CAT 5e FTP FRNC**

### General and environmental characteristics

Temperature range - operation	-20°C - +60°C
Temperature range - installation	+0°C - +50°C
Minimum bending radius - operation	20 mm
Minimum bending radius - installation	40 mm
Maximum pulling tension	80 N
Flame retardancy	IEC 332-1
Energy of flame	290 kJ/m
Weight (approx.)	27 kg/km
Maximum operating voltage	48 V rms
Maximum continuous current per conductor (25°C)	1.0 A

### Ordering information

**MARKING**

Text on the cable jacket                      Inkjet printing

**BELDEN 1868ENH (5) FLEX FTP CAT5E 4PR AWG26 LSNH ISO/IEC 11801 EN 50173  
100 OHM**

Meter marking:                                      Yes

**PAIR COLOR CODE**

Pair 1:            Blue-Black Ringband/Blue  
 Pair 2:            Orange-Black Ringband/Orange  
 Pair 3:            Green-Black Ringband/Green  
 Pair 4:            Brown-Black Ringband/Brown

**JACKET COLOUR**

Colour	RAL code	Belden colour code
Grey	RAL 7032	2634

**PACKAGING (PUT UP)**

Belden code	Delivery length	Weight	Remark
43055 xxxx 000	500 m	13,5 kg	Non returnable reel
43055 xxxx 250	1000 m	27,0 kg	Non returnable reel

xxxx: Belden colour code